

Home Cinema Projector

Vivitek HK2200

Ultra HD projector for the home cinema enthusiast



Features

- Ultra HD 4K (3,840 x 2,160) resolution for outstanding details and stunning visuals
- 2,000 lumens* for an amazing brightness
- Extremely high 18,000:1 contrast ratio for spectacular blacks and outstanding white colors
- Advanced video processor for fluid video streaming and programmable RGB colour adjustments VividMotion reduces fast-moving motion judder to create a fluid
- and flawless video stream
- High Dynamic Range (HDR10) and BT2020 compatibility for enriched brightness and impeccable vibrancy for precise natural colors
- Authentic and vibrant cinematic image quality with 100% REC709 and 80% DCI-P3 super-wide color gamut coverage
- Advanced Quad-Core CPU with 2GB RAM and 16GB internal memory (Approximately 11GB User Availability)
- Six segment RGBRGB color wheel delivers outstanding reds, greens and blue color reproductions
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- Vertical len shift for greater installation convenience and flexibility
- Wirelessly mirror content (Requires optional Wifi USB dongle (Sold seperatly)) from a connected smartphone, tablet or PC (iOS/MacOS/Windows/Android operating systems) without requiring any physical cables
- Display content directly from the projector's internal memory or simply plug in a flash drive (USB A) for untethered PC-free projection of office, photos, videos, and audio files
- Advanced HDMI 2.0 connectors for high quality digital video signals and quick data transfer rates
- Audio ready with built-in 5 watt speaker and audio out port Long lasting energy efficient lamps that last up to 15,000 hours
- (Dynamic Eco) Wide 1.3x zoom range and vertical lens shift for greater
- installation convenience and flexibility
- Full functioning remote control for easy control
- Secure a cable to the projector's security bar to prevent theft or unauthorized movement of the projector

Photos





vfiltak	592. water were	

1000	1.00	1	
-	40		
	- K	L	

PRELIMINARY SPECIFICATION FOR REFERENCE ONLY. SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. EXPECTED Q4/2019 MARKET AVAILABILITY.

Specifications

Specifica	lions			
Display Type		DLP [®] 0.47" TRP by Texas Instruments		
Brightness		2,000 Lumens*		
Native Resolution		UHD (3,840 x 2,160)		
Maximum Resolution		UHD (3,840 x 2,160)		
Contrast Ratio		18,000:1		
Lamp Life/Typ	е	4,000/10,000/15,000 Hours (Normal/Eco./Dynamic Eco), 245W		
Throw Ratio		1.13 - 1.47:1		
Image Size (D	iagonal)	0.8m - 7.62m (30" - 300")		
Projection Dist		0.95m – 7.6m (3.1ft - 25ft)		
Projection Len		F = 1.9 - 2.47 f = 12 - 15.6 mm		
Zoom Ratio*		1.3x		
Aspect Ratio		16:9		
Offset		100%±4%		
Vertical Scan Rate		23 - 120Hz		
Horizontal Frequency		15 - 135kHz		
Lens Shift Range		Yes (Vertical)		
3D Functionality		Yes (Via DLP® Link™, Blu-ray 3D)		
CPU Processor		ARM Quad Cortex - A53 CPU up to 1.5GHz		
GPU/CPU Processor		Mali™ T820-MPx		
Wireless (Via L	ISB Dongle)	MT7662T, 2.4GHz/5GHz, 802.11a/b/g/n/ac		
(Sold Separately)		EZC-5201BS, 2.4GHz/5GHz, 802.11a/b/g/n/ac		
Storage	RAM	2GB DDR3		
	Internal	16GB (eMMC Flash) (Approximately 11GB User Availability)		
	External	USB Flash Drive (Compatible up to 2GB)		
Speaker		5W (Mono)		
Computer Compatibility		VGA (640 x 480) to 4K UHD (3840 x 2160)		
Video Compatibility		480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p)		
East a data d	Docume nts	Office Microsoft [®] (Word, PowerPoint, Excel [®]), TXT, EPUB		
Embedded Media Player (Formats	Video	AVI, TS, MPG, MKV, MOB, RMVB, MOV, 3GP, ASF, DAT, MP4, TP, TRP, FLV, M2TS, F4V, MPEG, H265		
Supported)	Photo	JPEG, BMP, PNG		
	Audio	MP3, AAC, WAV, M4A		
I/O Connection Ports		HDMI v2.0 (x2), Audio-Out (Mini-Jack), S/PDIF Audio-Out, USB v3.0 Type A (5V/1.5A), USB v2.0 Type A (5V/1.5A), USB Type A Power (5V/1.5A), 12V Trigger, RS-232-In, USB (Service)		
Projection Method		Table Top, Ceiling Mount (Front or Rear)		
Security Solutions		Kensington [®] Security Slot		
Dimensions (V	VxDxH)	370 x 253 x 130mm (14.6" x 10" x 5.1")		
Weight		4.2kg (9.3lbs)		
Available Colo	ors	White		
Noise Level		33dB/29dB (Normal/Eco. Mode)		
Power Supply		AC 100-240V, 50/60Hz		
Power Consur	nption	350W (Max), <0.5W (Standby Mode)		
Standard		AC Power Cord, HDMI Cable, Remote Control,		
Accessories		Documentation Kit		
Optional Acce	ssories	Wifi USB Dongle		

*Note: Brightness specifications are in compliance with ISO 21118 standards ©2019 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.





HOMI