

PRELIMINARY SPECIFICATION FOR REFERENCE ONLY. SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. EXPECTED Q1/2020 PRODUCT LAUNCH.

Portable Projector

Vivitek DW275

WXGA projector with a brilliant image, multiple I/O ports and long-life lamp



Features

- Up to 4,000 lumens with a strong contrast ratio
- Native WXGA resolution with a maximum WUXGA resolution .
- DLP[®] and BrilliantColor[™] technologies for distinct and vibrant • images
- Low cost of ownership and maintenance with an energy efficient . lamp for up to 10,000 hours (Eco. Mode) of usage
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- Manual zoom and focus for easy adjustment and positioning flexibility
- Full suite of display connectivity inputs and outputs
- 2W of total stereo audio power with multiple audio-in and audio-out ports
- . Choose from 8 pre-set display modes to get the most suitable display image
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington[®] security slot, and security bar

Vative Resolution WXGA (1280 x 800) Maximum Resolution WUXGA (1,920 x 1,200) Contrast Ratio 15,000:1 amp Life/Type 5,000/10,000 Hours (Normal/Eco.), 210W Throw Ratio 1.55 - 1.86 mage Size (Diagonal) 40" - 300" Projection Distance 1.3m -10.2m (4.3ft - 33.5ft) Projection Lens F=2.42 - 2.62, f=22.5 - 25.79mm Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Commuter Compatibility Yes Appeater 2W (Mono) Connection Ports NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p // O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Solot, Keypad Lock <th>Display Type</th> <th>Single Chip 0.65" DLP Technology by TI</th>	Display Type	Single Chip 0.65" DLP Technology by TI
Maximum Resolution WUXGA (1,920 x 1,200) Contrast Ratio 15,000/1 Lamp Life/Type 5,000/10,000 Hours (Normal/Eco.), 210W Throw Ratio 1.55 - 1.86 Image Size (Diagonal) 40" - 300" Projection Distance 1.3m -10.2m (4.3ft - 33.5ft) Projection Lens F=2.42 - 2.62, f=22.5 - 25.79mm Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Connection Ports (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensin	Brightness	4,000 Lumens
Contrast Ratio 15,000:1 Lamp Life/Type 5,000/10,000 Hours (Normal/Eco.), 210W Throw Ratio 1.55 - 1.86 Image Size (Diagonal) 40" - 300" Projection Distance 1.3m -10.2m (4.3ft - 33.5ft) Projection Lens F=2.42 - 2.62, f=22.5 - 25.79mm Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Compatibility Yes NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080j 1080i, 1080p HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (wxbxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Cons	Native Resolution	WXGA (1280 x 800)
Instruction Instruction Lamp Life/Type 5,000/10,000 Hours (Normal/Eco.), 210W Throw Ratio 1.55 - 1.86 Image Size (Diagonal) 40" - 300" Projection Distance 1.3m -10.2m (4.3ft - 33.5ft) Projection Lens F=2.42 - 2.62, f=22.5 - 25.79mm Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Connection Ports (x2), Audio-In (Mini-Ja	Maximum Resolution	WUXGA (1,920 x 1,200)
Throw Ratio1.55 - 1.86Image Size (Diagonal)40" - 300"Projection Distance1.3m -10.2m (4.3ft - 33.5ft)Projection Lens $F=2.42 - 2.62$, f=22.5 - 25.79mmZoom Ratio1.2xAspect Ratio16:10Offset104%±5%Keystone CorrectionVertical:±40°Horizontal Frequency15 -102kHzVertical Frequency23 - 120Hz3D CompatibilityYesSpeaker2W (Mono)CompatibilityVGA (640 x 480) to WUXGA_RB(1920 x 1200)Video CompatibilityVGA (640 x 480) to WUXGA_RB(1920 x 1200)Video CompatibilityNTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p//O Connection PortsHDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service)Projection MethodTable Top, Ceiling Mount (Front or Rear)Security SolutionsKensington® Security Slot, Keypad LockDimensions (wxbxH)332 x 244 x 105mm (13" x 9.6" x 4.1")Weight2.6kg (5.7lbs)Available ColorsWhiteNoise Level32dB/29dB (Normal/Eco. Mode)Power Consumption250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)StandardAC Power Cord, VGA Cable, Remote Control,	Contrast Ratio	15,000:1
Image Size (Diagonal) $40" - 300"$ Projection Distance $1.3m -10.2m (4.3ft - 33.5ft)$ Projection Lens $F=2.42 - 2.62$, $f=22.5 - 25.79mm$ Zoom Ratio $1.2x$ Aspect Ratio $16:10$ Offset $104\% \pm 5\%$ Keystone CorrectionVertical: $\pm 40^{\circ}$ Horizontal Frequency $15 - 102 \text{ KHz}$ Vertical Frequency $23 - 120 \text{ Hz}$ 3D CompatibilityYesSpeaker $2W$ (Mono)Computer CompatibilityVGA (640 x 480) to WUXGA_RB(1920 x 1200)Video CompatibilityVGA (640 x 480) to WUXGA_RB(1920 x 1200)Video CompatibilityNTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p//O Connection PortsHDMI v1.4b (x2), Composite Video, S-Video, VGA-In//O Connection PortsKensington® Security Slot, Keypad LockDimensions (WxDxH) $332 x 244 x 105mm (13" x 9.6" x 4.1")$ Weight $2.6kg (5.7lbs)$ Available ColorsWhiteNoise Level $32dB'29dB$ (Normal/Eco. Mode)Power Consumption $250W$ (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Lamp Life/Type	5,000/10,000 Hours (Normal/Eco.), 210W
Image Size (Diagonal) $40" - 300"$ Projection Distance $1.3m -10.2m (4.3ft - 33.5ft)$ Projection Lens $F=2.42 - 2.62$, $f=22.5 - 25.79mm$ Zoom Ratio $1.2x$ Aspect Ratio $16:10$ Offset $104\% \pm 5\%$ Keystone CorrectionVertical: $\pm 40^{\circ}$ Horizontal Frequency $15 - 102 \text{ KHz}$ Vertical Frequency $23 - 120 \text{ Hz}$ 3D CompatibilityYesSpeaker $2W$ (Mono)Computer CompatibilityVGA (640 x 480) to WUXGA_RB(1920 x 1200)Video CompatibilityVGA (640 x 480) to WUXGA_RB(1920 x 1200)Video CompatibilityNTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p//O Connection PortsHDMI v1.4b (x2), Composite Video, S-Video, VGA-In//O Connection PortsKensington® Security Slot, Keypad LockDimensions (WxDxH) $332 x 244 x 105mm (13" x 9.6" x 4.1")$ Weight $2.6kg (5.7lbs)$ Available ColorsWhiteNoise Level $32dB'29dB$ (Normal/Eco. Mode)Power Consumption $250W$ (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Throw Ratio	1.55 - 1.86
Projection Distance 1.3m -10.2m (4.3ft - 33.5ft) Projection Lens F=2.42 - 2.62, f=22.5 - 25.79mm Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility Yes NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p I/O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (wxbxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)		
Projection Lens F=2.42 - 2.62, f=22.5 - 25.79mm Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical:±40° 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p I/O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,		
Zoom Ratio 1.2x Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p VO Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-Int (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)		
Aspect Ratio 16:10 Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p //O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-Int (X2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,	Zoom Ratio	,
Offset 104%±5% Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p //O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (wxbxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,	Aspect Ratio	
Keystone Correction Vertical:±40° Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080p I/O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (X2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WXDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Offset	
Horizontal Frequency 15 -102kHz Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p I/O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Keystone Correction	
Vertical Frequency 23 - 120Hz 3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p I/O Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)		
3D Compatibility Yes Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)		
Speaker 2W (Mono) Computer Compatibility VGA (640 x 480) to WUXGA_RB(1920 x 1200) Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p VO Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-Int (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption Z50W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)		Yes
Video Compatibility NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p VO Connection Ports HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption Z50W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,	Speaker	2W (Mono)
Video Compatibility 1080i, 1080p INDREAD HDMI v1.4b (x2), Composite Video, S-Video, VGA-Int (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Supply AC 100-240V, 50/60Hz Power Consumption (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,	Computer Compatibility	VGA (640 x 480) to WUXGA_RB(1920 x 1200)
I/O Connection Ports (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service) Projection Method Table Top, Ceiling Mount (Front or Rear) Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (WxDxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Video Compatibility	
Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (wxbxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Supply AC 100-240V, 50/60Hz Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	I/O Connection Ports	
Security Solutions Kensington® Security Slot, Keypad Lock Dimensions (wxbxH) 332 x 244 x 105mm (13" x 9.6" x 4.1") Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Supply AC 100-240V, 50/60Hz Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Projection Method	Table Top, Ceiling Mount (Front or Rear)
Weight 2.6kg (5.7lbs) Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Supply AC 100-240V, 50/60Hz Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Security Solutions	
Available Colors White Noise Level 32dB/29dB (Normal/Eco. Mode) Power Supply AC 100-240V, 50/60Hz Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Dimensions (WxDxH)	332 x 244 x 105mm (13" x 9.6" x 4.1")
Noise Level 32dB/29dB (Normal/Eco. Mode) Power Supply AC 100-240V, 50/60Hz Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Weight	2.6kg (5.7lbs)
Power Supply AC 100-240V, 50/60Hz Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)	Available Colors	White
Power Consumption 250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,	Noise Level	32dB/29dB (Normal/Eco. Mode)
Power Consumption (Standby Mode) Standard AC Power Cord, VGA Cable, Remote Control,	Power Supply	AC 100-240V, 50/60Hz
	Power Consumption	
	Standard	
	Accessories	

their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.





Photos











