



Multimedia Projector

Vivitek DU3661Z

High performance WUXGA laser projector with HDBase™, bright 5,000 ANSI lumens and a full suite of displays ports



Features

- 5,000 ANSI lumens with a dynamic 3,000,000:1 contrast ratio for an amazing image quality
- Solid-state laser phosphor light source for reliable projection and performance
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- Environmentally friendly lamp-less design with an operating time up to 20,000 hours
- Manual zoom and focus for easy adjustment and positioning flexibility
- Vertical lens shift and 1.5x zoom ratio for greater installation convenience and flexibility
- Project 3D content from DLP® Link™, and BluRay HDMI 1.4b for realistic life-like images
- Built-in 10W audio speaker with multiple audio-in and audio-out ports
- 360° operation and projection design for set up in all angles
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Quick on/off for immediate power on or shut down
- Anti-theft security features include: Kensington® security slot, security bar, and password protected keypad lock

Specifications

Display Type	Single Chip 0.67" DLP Technology by TI
Brightness	5,000 ANSI Lumens
Native Resolution	WUXGA (1920 x 1200)
Maximum Resolution	WUXGA (1920 x 1200)@60Hz
Contrast Ratio	3,000,000:1
Laser Life/Type	20,000 + hours (Laser Phosphor Light Engine)
Throw Ratio	1.39 - 2.09:1
Image Size (Diagonal)	25.9" - 324.9"
Projection Distance	1.2m - 10m (3.9ft - 32.8ft)
Projection Lens	F#2.42 - 2.97, f=20.7 - 31.05mm
Zoom Ratio	1.5x
Aspect Ratio	16:9
Offset	130%/115%
Keystone Correction	Vertical/Horizontal ±30°
Horizontal Frequency	15, 31 - 91.4kHz
Vertical Frequency	24 - 30Hz, 47 - 120Hz
3D Compatibility	Yes (DLP® Link™, HDMI 1.4 (Blu-Ray 3D))
Speaker	10W (Mono)
Lens Shift	Yes (Vertical)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4 (x3), VGA-In, Audio-In (Mini-Jack), Audio-In RCA (L/R), VGA-Out, Audio-Out (Mini-Jack), USB Type A Power (5V/1.5A), HDBase™, RJ45 (Lan), RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	Estimated 395 x 338 x 126mm (15.5" x 13.3" x 4.9")
Weight	Estimated 7kg (15.4lbs)
Available Colors	White
Noise Level	35dB/29dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	330W (Normal Mode), 270W (Eco. Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	N/A

©2019 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

Photos

